



- Main
- Observations
- Requests
- Deliveries
- Transfer
- Help
- Logout

View Library

- Display**
- Relationships
- [Deliveries](#)
- [Prime/Rider](#)
- Export
- [XML](#)
- [Summary-](#)
- [Text](#)
- [APF](#)
- Comments
- [View](#)
- [Add](#)
- Page
- [Legend](#)
- [Help](#)

This request revision is contained in a delivery and is frozen. Changes must be saved as a new revision.

Request Header [Description](#) [Observations](#) [Files](#) [Steps](#)

ID:	RSS_028SA_OCCORT002_RSS	
Title:	RSS Operational Readiness Test	Revision: 1
Rev Created:	28 Jul 2005, 10:03, by Goltz, Gene L	Priority: 2
Updated:	28 Jul 2005, 10:13, by Goltz, Gene L	Comments: 0
Start Time:	2006-255T09:57:00 GMT	
Pre Start	001T12:00:00	
Tolerance:		
Post Start	003T12:00:00	
Tolerance:		
Duration:	000T11:05:00	
End Time:	2006-255T21:02:00 GMT	
Change:	original	
Change Justification:		
Visibility:	Public	
SPASS Type:	SPASS Rider (Collaborative: No)	
Group Filter:	AWG	
Contact Info:	Aseel Anabtawi, 393-1073	
Description:	RSS Operational Readiness Test (ORT). Pointing=XBAND to Earth. Required to be tracked by DSS-14, DSS-43, and DSS-63.	

Request Description [Header](#) [Observations](#) [Files](#) [Steps](#)

Pointing Information			
Pointing:	XBAND to Earth		
Agreement:			
Primary Pointing:	XBAND to Earth		
Secondary Pointing:	PIC		
Resources			
Sequence Type:	Background	SSR Data Class:	Normal
Op Mode:	RSS2/RWA	Telem Mode:	-
Power (watts):	41.7	Est CDS Words:	200
Rate Multiplier:		APGEN Rate:	0
Effective Rate:	0 bps	Data Volume:	0 x 10 ⁶ bits
Frames:		Bits Per Frame:	
Team Consumables:	Ka-TWTA and KEX on at start; off at end. KAT thermal cycles incurred=0.0625		
IEB Text:			
Apgen Fields			
Activity Type:	RSS Activity		
Attributes		Parameters	
Legend:	RSS	CDSWords:	200
Duration:	000T11:05:00	Power:	41.7
Color:	Hot Pink	SSRDataClass:	Normal
Pattern:	60 - Large Pinwheels		

Description: [see above](#)

Green items are request fields shown here for clarity

Support and Other Descriptive Information

Liens:

Waivers:

RTC:

FSW Loads:

ITL Request:

Special DSN Requirements: DSS-14, DSS43, and DSS-63 required to obtain X- and S-band downlink data.

Special Requirements: This activity will need the RSS S-band frequency (RSS2_RWAF) Op Mode. IO-RS Ops should be consulted, along with the integrated and approved activities TOL, before SASF generation.

Support Imaging Required:

Document References:

As Flown:

SASF Fields

Processor:

Key:

Workgroup:

Status:

Upper Label:

Lower Label:

Edit Group:

Request State:

Associated Observations [Header](#) [Description](#) [Files](#) [Steps](#)

Last Updated	Observation	Rev	Cmts

Associated External Files [Header](#) [Description](#) [Observations](#) [Steps](#)

File Name	Relative Path	Last Modified	File Size

Steps [Header](#) [Description](#) [Observations](#) [Files](#)

Type	Label	Name	Offset	Off-Type