



- Main
- Observations
- Requests
- Deliveries
- Transfer
- Help
- Logout

View Library

- Display**
- Relationships
- [Deliveries](#)
- [Prime/Rider](#)
- Export
- [XML](#)
- [Summary-](#)
- [Text](#)
- [APF](#)
- Comments
- [View](#)
- [Add](#)
- Page
- [Legend](#)
- [Help](#)

This request revision is contained in a delivery and is frozen. Changes must be saved as a new revision.

Request Header [Description](#) [Observations](#) [Files](#) [Steps](#)

ID:	RSS_189SA_OCCORT001_RSS	
Title:	RSS Operational Readiness Test	Revision: 1
Rev Created:	10 Nov 2011, 14:34, by Anabtawi, Aseel	Priority: 2
Updated:	10 Nov 2011, 14:35, by Anabtawi, Aseel	Comments: 0
Start Time:	2013-127T07:47:00 GMT	
Pre Start	001T12:00:00	
Tolerance:		
Post Start	003T12:00:00	
Tolerance:		
Duration:	000T09:00:00	
End Time:	2013-127T16:47:00 GMT	
Change:	created from copy	
Change Justification:		
Visibility:	Public	
SPASS Type:	SPASS Rider (Collaborative: No)	
Group Filter:	MAPS	
Contact Info:	Aseel Anabtawi, 393-1073	
Description:	RSS Operations Readiness Test (ORT), to demonstrate DSN and RSSG preparedness to support the Rev190 Saturn rings occultation on 2013/140.	
	DSS-34 required for X- and Ka-band support.	

Request Description [Header](#) [Observations](#) [Files](#) [Steps](#)

Pointing Information			
Pointing:	XBAND to Earth		
Agreement:			
Primary Pointing:	XBAND to Earth		
Secondary Pointing:	PIC		
Resources			
Sequence Type:	Background	SSR Data Class:	Normal
Op Mode:	RSSK	Telem Mode:	-
Power (watts):	38.7	Est CDS Words:	200
Rate Multiplier:		APGEN Rate:	0
Effective Rate:	0 bps	Data Volume:	0 x 10 ⁶ bits
Frames:		Bits Per Frame:	
Team Consumables:	Ka-TWTA and KEX on at start; off at end. KAT thermal cycles incurred=0.2500		
IEB Text:			
Apgen Fields			
Activity Type:	RSS Activity		
<u>Attributes</u>		<u>Parameters</u>	
Legend:	RSS	CDSWords:	200
Duration:	000T09:00:00	Power:	38.7
Color:	Hot Pink	SSRDataClass:	Normal

Pattern: 60 - Large Pinwheels
 Description: see above

Green items are request fields shown here for clarity

Support and Other Descriptive Information

Liens:
 Waivers:
 RTC:
 FSW Loads:
 ITL Request:
 Special DSN Requirements: DSS-34 required to obtain X- and Ka-band downlink data.
 Special Requirements: This activity will need to start with the RSS PIM Warm-Up Opmode (RSSP_RWAF), and be followed 5 minutes later with the RSS Ka-frequency Opmode (RSSK, SLOW an option). IO-RS Ops should be consulted, along with the integrated and approved activities TOL, before SASF generation.
 Support Imaging Required:
 Document References:
 As Flown:

SASF Fields

Processor:
 Key:
 Workgroup:
 Status:
 Upper Label:
 Lower Label:
 Edit Group:
 Request State:

Associated Observations [Header](#) [Description](#) [Files](#) [Steps](#)

Last Updated	Observation	Rev	Cmts

Associated External Files [Header](#) [Description](#) [Observations](#) [Steps](#)

File Name	Relative Path	Last Modified	File Size

Steps [Header](#) [Description](#) [Observations](#) [Files](#)

Type	Label	Name	Offset	Off-Type